

## Image<sup>®</sup> 600 Laminators

A cost effective way to capitalize on profitable, large-format display opportunities, the Image 600 offers you full-featured finishing capabilities up to 61" (155 cm) wide.

The Image 600 is capable of cold or heat-activated overlaminating and hot sealing. Ideal for finishing ink jet, photographic and electrostatic prints.

## Image<sup>®</sup> 600-S Laminators

The Image 600-S features a heated top roller and offers complete pressure-sensitive mounting and laminating and two-pass hot sealing up to 61" (155 cm) wide, making it perfect for wide format ink jet prints.

## Primary Applications

The SEAL 600 and 600-S offer pressure-sensitive mounting and heat-activated mounting and laminating; Heat-assisted, and heat-activated mounting and laminating; and hot sealing in one pass with the 600 model and 2 passes with the 600-S.



## Features

- High-release silicone rollers for easy cleaning
- Pneumatic pressure adjustment with fine-tune control for a smooth finish
- Electric heat with digital controls for even heating and maximum accuracy
- Dial-in roller height adjustment for fast, accurate nip setting
- Vacuum feed table for flat, wrinkle-free feeding of digital prints
- Cooling fans for smooth output when encapsulating
- Swing-out supply shafts with brakes for easy loading and precise film tension adjustment
- Digital media roll easel for convenient roll-to-roll laminating
- Automatic upper take-up shaft for removing release lines
- Easy-to-use controls & foot pedal for hands-free operation
- Comprehensive safety systems with emergency stops and electric eyes
- Floor cart with wheels

# Image® 600 Laminators

## SPECIFICATIONS

Specifications	Image® 600	Image® 600-S
Maximum Working Width	61" (155 cm)	61" (155 cm)
Maximum Working Width (heated encapsulation)	55" (140 cm)	55" (140 cm)
Maximum Speed	10 fpm (3.1 mpm)	10 fpm (3.1 mpm)
Maximum Roll Opening	1 1/8" (29 mm)	1 1/8" (29 mm)
Maximum Roll Temperature	250°F (121°C)	250°F (121°C)
Dimensions	78"w x 32"d x 50"h 198 cm x 81 cm x 127 cm	78"w x 32"d x 50"h 198 cm x 81 cm x 125 cm
Net Weight	550 lbs. (251 kg)	550 lbs. (251 kg)
Shipping Weight	850 lbs. (389 kg)	850 lbs. (389 kg)
Mechanical Requirements	2 CFM compressed air @ 100 psi, 0.25" (0.6 cm) ID flex. line	2 CFM compressed air @ 100 psi, 0.25" (0.6 cm) ID flex. line
Electrical Requirements*	208-240 VAC 50/60 Hz, single phase, 30 Amp or 380-415 VAC 50/60 Hz, three phase, 15 Amp	208-240 VAC 50/60 Hz, single phase, 15 Amp
Maximum Power Consumption	7,200 Watts	3,600 Watts

\* Important: SEAL recommends that your laminator be installed by a licensed electrician in accordance with electrical codes in your area. Specifications subject to change without notice

Image® and SEAL® are registered Brands of Hunt Corporation

**Seal Graphics Americas Corporation**  
1667 Knecht Avenue  
Suite J  
Baltimore, MD 21227  
Tel: 410-242-5968  
Fax: 410-242-1750

**Seal Graphics Canada**  
690 Gana Court  
Mississauga, Ontario  
Canada, L5S 1P2  
Tel: +905 564 7717  
Fax: +905 564 7094

**Seal Graphics U.K. Ltd**  
Unit 1, 1 Watkins Close  
Burnt Mills Industrial Estate  
Basildon, Essex SS13 1BJ  
United Kingdom  
Tel: +44 1268 530 331  
Fax: +44 1268 729 442

**Seal Graphics Europe BV**  
Kanaaldijk O.Z.3  
P.O.Box 29,  
8100 AA Raalte  
The Netherlands  
Tel: +31 572 345 500  
Fax: +31 572 345 501

**Seal Graphics Pacific Limited**  
Unit A, 13th Floor, Block 1  
Leader Industrial Centre  
Tsuen Wan,  
New Territories, Hong Kong  
Tel: +852 2407 3738  
Fax: +852 2408 0973

Contact your local distributor:

